



## Efficient feeding

of products for film packaging and print finishing

## **Peripherals Feeders**

feeding, grouping, stacking, rejecting, turning and marking of products



The processing makes the difference





## Feeder programme

Capacity cycles/h	Product size
up to 15,000	Length: 50 – 230 mm Width: 90 – 330 mm Height: up to 3 mm
Also available in	double function
up to 18,000 in 2 capacity ranges	Length: 70 – 400 mm Width: 90 – 440 mm Height: up to 8 mm
Capactiy cycles/h	<b>Product size</b>
up to 60,000	Length: 50 – 330 mm Width: 50 – 250 mm Height: up to 3 mm
up to 18,000	Length: 50 – 450 mm Width: 70 – 370 mm Height: up to 3 mm
Capactiy cycles/h	Product size
up to 18,000 in 2 widths	Length: 148 – 420 / 520 mm Width: 105 – 315/ 450 mm Height: 2 – 60 mm
	cycles/h  up to 15,000  Also available in up to 18,000 in 2 capacity ranges  Capactiy cycles/h  up to 60,000  Capactiy cycles/h  up to 18,000

Pick and Place feeders	Capacity cycles/h	Product size
PP 250	up to 15,000	Length: 50 – 200 mm Width: 50 – 150 mm Height: 0,5 – 6 mm
Newspaper feeders	Capacity cycles/h	Product size
ZA 450	up to 10,000	Length: 300 – 450 mm Width: 300 – 450 mm Height: up to 30 mm

▼	•	
Flat stacking feeder	Capacity cycles/h	Product size
FSA 380 Z perfect for photographic paper	up to 50,000	Length: 120 – 420 mm Width: 100 – 380 mm Paper weight: 60 – 250 g/m <sup>2</sup>

All dimensions refer to the feeding direction.

All feeders can be delivered in a moveable version and used as stand-alone module.

## **Further feeders and peripherals**

- Magazines for books, CD's, discs, etc.
- Automatic stack loader for magazines
- Shingle loading for all feeders
- Stack loading conveyor for universal feeder
- Front page opener
- Plough opener
- Routing label feeder with or without printer
- Booklet feeder
- Special feeders
- Infeed rail with counting function
- Collator
- Addressing systems
- Inkjet and camera systems
- Stacking unit