# Pharmaceutical folder as Stand-alone folding system





### Set-up by pushing a button:

- Automatic fold plate setting
- Automatic fold roller setting
- Automatic positioning of code reading heads
- 16 standard folds are programmed
- Other folds are freely programmable
- Memory for 200 repetitive jobs
- Interface: Ethernet TCP/IP/FTP

#### **Benefits:**

- No calculating of stop positions
- No removal of fold plates
- No need to install deflectors
- Short walking distances

# leafletFOLDER NET 21

The computer control simplifies machine operation. A touch-screen is the interactive operator interface where all important settings are made.

After the paper size and the type of fold have been entered, the fold plate stops and deflectors move to their calculated positions by pushing a button. The fold rollers are also set automatically.



The basis for this is the chosen type of fold and the predetermined paper thickness. Setting up saved jobs is even more

user-friendly, because all individual corrections are considered and accurately reproduced.

Besides the settings of fold plate stops, deflectors, fold rollers and reading heads the data for speed, counter and kicker are also predetermined. Short set-up times Simple operation A minimum of waste

Paper sizes:

Version I: max. 216 x 320 mm min. 75 x 85 mm Version II: max. 216 x 600 mm min. 75 x 85 mm

Fold length: max. 225 mm; min. 15 mm

Paper weight: 40 to 180 GMS

Speed: 240 m per minute (depending on material)

Electrical: 3 x 400 V / 50 Hz / N / PE

## Folding better automatically.

## **Optimised equipment**



#### Feeder with swivel-mounted pile table

- Separates both unfolded and pre-folded sheets
- Stack height up to 2,500 sheets (DIN A4; 50 GSM)
- Replenishment from the top without machine stop
- Swivel-mounted, therefore good accessibility for maintenance jobs
- Pile table available in two versions: for paper sizes up to a length of 320 mm for paper sizes up to a length of 600 mm



- **Fold rollers**
- Polyurethane-steel-fold rollers with self-cleaning effect
- Long service life
- Automatically adjustable
- Driven by low-noise and almost maintenance-free flat belts



#### Fold plates

- Four automatically adjustable fold plates with integrated automatic deflectors
- Deflectors with uninterrupted surfaces prevent marks on paper
- Electrical connection is achieved automatically, no more tangled cables and plugs



**Touch technology** 


#### Simple



Fast



### Convenient






#### Small format vertical stacker SKM 36

- Prevents small folds from opening up
- Infeed width: max. 360 mm; min. 50 mm
- Smallest fold length: 16 mm

## **Optional equipment**

- Reading heads for oneor two-sided reading
- Professional scoring device
- Diverter after the fold unit

Floor space



leafletFOLDER NET 21 with SKM 36



# Folding better automatically.