

Technical specifications

| Multinak S | | |
|---|---|--|
| Type of stapling heads | A | B |
| Number of stapling heads | 2 | 2 |
| Min. distance between stapling heads (mm) | 80 | 80 |
| Max. distance between stapling heads (mm) | 155 | 155 |
| Brochures | from 2 sheets (80 gsm) | from 2 sheets (80 gsm) |
| Pads up to approx. | 150 sheets (80 gsm) | 270 sheets (80 gsm) |
| Staple leg length (mm) | 6 – 18 | 6 – 30 |
| Staple types | 24, 26, 30 | 50, B 50 |
| Loop staples | yes | no |
| Staple magazine per head | type 30 = 500 staples type 26 = 400 staples type 24 = 300 staples | type 50 = 400 staples type B 50 = 300 staples |
| Throat depth (mm) | | |
| Brochures | 310 | 310 |
| Pads | 150 | 150 |
| Clamps for small formats | ✓ | ✓ |
| Extension table with back stop bar | • | • |
| Weight net / gross (kg) | 100 / 111 | 100 / 111 |
| Power supply | 230 V / 50 Hz or 400 V / 50 Hz | 230 V / 50 Hz or 400 V / 50 Hz |
| Available with foot treadle (no power supply) | • yes (model FS) | • yes (model FS) |
| H x W x D operational (cm) | 110 x 60 x 75 128 x 60 x 75 (treadle version) | 110 x 60 x 75 128 x 60 x 75 (treadle version) |
| H x W x D packed (cm) | 130 x 75 x 75 150 x 75 x 75 (treadle version) | 130 x 75 x 75 150 x 75 x 75 (treadle version) |