



Bergmannstrasse 10  
 88471 Laupheim/Germany  
 Phone +49 (0)7392/97 25-0  
 Fax +49 (0)7392/97 25-50  
 Email info@pernuma.de  
 Web www.pernuma.de



## PERNUMA PERFOSET E/P, ES/P Electric Embossing Machines

for securing official documents or photographs in passports; also for embossing certificates, sheets of writing paper, business cards, etc. without applying any physical force.

Our electric embossing machines were designed for satisfying high demands. Even in more solid materials like cardboard or pasteboard and with bigger embossing stamps you will easily obtain needle-sharp impressions.

The insertion depth is 105 mm from the paper edge to the center of the impression.

In order to enable exact positioning of every imprint on its corresponding forms, the machines are by production-line supplied with adjustable stops for side and depth.

The upper stamp is engraved in brass or steel. The lower stamp is made of plastic.

### PERNUMA PERFOSET E/P

A very robust, electrical embossing machine for office use, supplied with a modern NC motor.

Stamp diameter can be up to 75 mm.

The embossing is released by pressing a push button on the side of the machine.

### PERNUMA PERFOSET ES/P

This electrical high performance machine is supplied production-line with an especially strong gear unit in order to enable mass embossing and continuous operation. It meets highest demands.

Stamp diameter can be up to 80 mm.

The embossing is released by pressing a pedal which is supplied by standard.

PERFOSET ES/P is one fixed unit on metal stand.

### Important

In order for the imprint to appear legible in the appropriate place on your forms, please include relevant information in your order.



Bergmannstrasse 10  
88471 Laupheim/Germany  
Phone +49 (0)7392/97 25-0  
Fax +49 (0)7392/97 25-50  
Email info@pernuma.de  
Web www.pernuma.de



## PERNUMA PERFOSET E/P, ES/P Electric Embossing Machines

### Technical Data

Drive:  
Power supply:

### PERNUMA PERFOSET E/P

Electric  
AC 230 V  
Special voltage possible

### PERNUMA PERFOSET ES/P

Electric  
AC 230 V or three-phase  
current 230/400 V  
Special voltage possible

Insertion depth  
Maximum stamp diameter  
Thickness of female die  
Diameter of spigot  
Length of spigot:  
Thickness of male die

105 mm  
75 mm  
12 mm  
12 mm  
20 mm  
5 mm

105 mm  
80 mm  
12 mm  
12 mm  
20 mm  
5 mm

Net weight / Gross weight

26 kg / 28 kg

90 kg / 140 kg

Packaging:  
Packaging dimensions

Carton  
59 x 39 x 27 cm

Wooden case  
120 x 49 x 92 cm

### Extra Equipment:

- Foot switch (PERFOSET E/P)
- Automatic release
- Stroke counter for counting number of embossing completed
- Safety lock (preventing unauthorized persons from working with the machine)
- Table
- Fixed or special stops



Stamp diameter  
PERFOSET E/P max. 75 mm  
PERFOSET ES/P max. 80 mm

