ROLLSROLLER® Flatbed Applicator 400



The ROLLSROLLER® Flatbed Applicator enables a single person to apply all types of self-adhesive vinyl, applicator film and protective laminate in just a few minutes. It gives you complete control over positioning and produces results that are free from bubbles and creases.


ROLLSROLLER® 400 is designed for customers with limited space.



Fast, easy and precise



Easy to laminate from roll to medium.



Fast and precise dry application to surface.



Media holder for end of bed is a practical option.



Ergonomic working height.



Even better ergonomics if you choose a height-adjustable ROLLS-ROLLER®.



Practical side pockets for textile media.

ROLLSROLLER® Flatbed Applicator 400

	ROLLSROLLER® 400/150	ROLLSROLLER® 400/170
Overall length	4000 mm	4000 mm
Overall width	1760 mm	1960 mm
Bed width	1500 mm	1700 mm
Overall height	1520 mm	1520 mm
Length of working area	3600 mm	3600 mm
Width of working area/roller	1400 mm	1630 mm
Working height, standard model	920 mm	920 mm
Weight	650 kg	725 kg
Bed surface	Glass	Glass
Cutting mat, 5 mm	Yes	Yes
Side pockets	Yes	Yes
Illumination	9x36W fluorescent tubes	12x36W fluorescent tubes
Voltage	230 volt / 50 Hz	230 volt/50 Hz
Air pressure	Max. 6 bar	Max. 6 bar
Height adjustment, 750–1100 mm	Option	Option
Additional boom and roller	Option	Option
Low-noise compressor, 45 db	Option	Option
Media holder for end of bed	Option	Option

The ROLLSROLLER® Flatbed Applicator is preassembled at the factory. This means that a forklift truck will be required at the time of delivery with forks at least 1600 mm long and sufficient capacity to lift the ROLLSROLLER® model supplied.

