

DIBIPACK 3246 STX e 4255 STX

SHRINK-WRAPPING WITHIN REACH OF ALL



The most efficient and unexpensive shrink-wrappers around the world. Conceived and designed in order to be the best answer to the increasing demand of a simple and efficient shrink-wrapper with contained costs but great reliability. Ideal for fulfilling the various wrapping and packaging requirements of offices, banks, laboratories, archives, shops, newsagents, stationeries, bookshops, video- and musicshops, storehouses, wholesalers, pasta producers, bakers, a.s.o. They can be used also to make plastic envelopes.

- "one-step®" system: simultaneous sealing and shrinking
- two possible working programs: sealing+shrinking and sealing only.
- Traditional electronic control panel: sealing time, air temperature and time of hood closing adjustable by hand
- Hold-down solenoid (the hood remains closed up to the end of shrinking) and starting control with proximity included
- Unit-counter included
- Low maintenance
- Reduced energy consumption
- Reduced overall machine dimensions: it is not necessary a tunnel.
- Easily transportable: machine stand equipped with wheels on request
- Stand and Scrap-rewind on request

The machine works with hot thermo-sealing and shrinkable films such as PVC (**BLUE FILM**) and/or polyolefin films (**GREEN FILM – GOLDEN FILM**)

Machine made according to CE rules.

SPECIFICATIONS	Dibipack3246STX	Dibipack4255STX
Power supply	230 V - 1 Ph	230 V - 1 Ph
Power required	2.1 kW	3 kW
Overall dimensions L x W	1120 x 680 mm	1270 x 780 mm
Working plate height (on stand)	920 mm	920 mm
Machine weight	71 Kg	87 kg
Sealing Area W x L	320 x 460 mm	420 x 550 mm
Altezza max prodotto	200 mm	200 mm
Impulse sealing System	bottom blade	bottom blade
Max roll dimensions DIA x W	250 x 470 mm	250 x 600 mm
Output	4-6 pc/min	4-6 pc/min

notes: Technical data subject to variations without prior notice
Output depends on the operator and the type of the package