

DIBIPACK 3246 EV

THE EVOLUTION OF 'ONE-STEP[®]' SYSTEM

The evolution of “one-step[®]” shrink-wrap systems to offer great flexibility in applications but ease of operation and to grant high performances thanks to **some innovative patented devices**. Ideal solution for medium output requirements.

- Working Cycle electronically controlled by a microprocessor
- Automatic adjustment of sealing-time: the machine adjusts the sealing-time automatically according to the packaging speed.
- It is possible to memorize 8 different working programs
- Energy-saving function: the machine goes in “stand-by” if it does not work for a recordable period
- Possibility to start shrinking when sealing is completed
- Hold-down solenoid: the hood remains closed up to the end of shrinking.
- Starting control with proximity
- Hood may be released after fan stopping to avoid the escape of hot air at the end of the cycle
- Unit counter
- Reopening system through gas spring
- Scrap-rewind on request
- The machine works with PVC, polyolefin hot thermo-sealing and also shrinkable films.



Machine made according to CE rules.

| SPECIFICATIONS | DIBIPACK 3246 EV |
|----------------------------------|------------------|
| Power supply | 230 V - 1 Ph |
| Maximum power required | 2,1 KW |
| Overall machine dimensions L x W | 1120 x 680 mm |
| Working plate height (on stand) | 920 mm |
| Machine weight | 71 kg |
| Sealing area W x L | 320 x 460 mm |
| Maximum product height | 200 mm |
| Impulse sealing system | Bottom blade |
| Maximum roll dimensions DIA x W | 250 x 470 mm |
| Output | 4 - 6 pcs/min |

Note: Technical data subject to variations without prior notice
Output depends on the operator and the type of article to be wrapped.