



## DIBIPACK 4255 SA EV

### AT THE TOP OF HEAT-SHRINK WRAPPERS

In line with the company's motto "*innovation, ease of use and flexibility in applications*" Italdibipack presents these simplified shrink wrappers with **automatic working cycle** in order to grant higher performances and remarkable outputs. A further step towards more automation thanks to a stainless steel out feed conveyor, height adjustable, designed and conceived by Italdibipack R&D Team.

- Working Cycle electronically controlled by a microprocessor
- Automatic adjustment of sealing-time: the machine adjusts the sealing-time automatically according to the packaging speed.
- It is possible to memorize 8 different working programs
- Energy-saving function: the machine goes in "stand-by" if it does not work for a recordable period
- Possibility to start shrinking when sealing is completed
- Hold-down solenoid: the hood remains closed up to the end of shrinking.
- Starting control with proximity
- Hood may be released after fan stopping to avoid the escape of hot air at the end of the cycle
- Unit counter
- Reopening system through gas spring
- Stainless steel-mesh out feed conveyor belt automatically controlled by a timer and adjustable in height
- Activated carbon filter aspirator
- An automatic release of the conveyor belt can permit the film separation from the sealing blade after shrinking (patented)
- Scrap-rewind on request
- The machine works with PVC, polyolefin hot thermo-sealing and also shrinkable films.



Machine made according to CE rules.

| SPECIFICATIONS                   | DIBIPACK 4255 SA EV |
|----------------------------------|---------------------|
| Power supply                     | 380 V- 3 Ph         |
| Maximum power required           | 5,5 KW              |
| Overall machine dimensions L x W | 1800 x 800 mm       |
| Working plate height (on stand)  | 920 mm              |
| Machine weight                   | 120 kg              |
| Sealing area W x L               | 420 x 550 mm        |
| Maximum product height           | 200 mm              |
| Impulse sealing system           | Bottom blade        |
| Maximum roll dimensions DIA x W  | 250 x 600 mm        |
| Output                           | 4 - 8 pcs/min       |

**Note: Technical data subject to variations without prior notice**  
Output depends on the operator and the type of article to be wrapped.