

## ECOFARD 700 AA

**SLEEVE-WRAPPER WITH AUTOMATIC FEEDING: TO PRODUCE MORE !**

A sleeve-wrapper with the same specifications as the *Ecofard 700 SA* model but **with automatic feeding to make even more multipacks of different size of various products** (bottles, vases, jars, pots, cans, phials, cases etc) **and/or to protect boxes** integrating and/or replacing the use of carton boxes at end-of-line with great management advantages. **Two different models are available: compact (MB)** where the tunnel is connected with the sealing area, **and sealer-plus-tunnel (BB)** where the sealing area is independent from the tunnel. The machine works in a very simple way: a pneumatic pusher drives the products from the loading area towards the sealing area. Then a transversal sealing-bar (that has a pneumatic movement and temperature is electronically controlled) cuts and seals the film.

| SPECIFICATIONS                       | ECOFARD 700 AA MB     | ECOFARD 700 AA BB     |
|--------------------------------------|-----------------------|-----------------------|
| Power supply                         | 230/380 V             | 230/380 V3 Ph         |
| Power required                       | 17 KW                 | 21 KW                 |
| Overall machine dimensions L x W x H | 3000 x 1150 x 1850 mm | 4300 x 1180 x 2020 mm |
| Working plate height                 | 820 mm                | 870 mm                |
| Tunnel entrance dimensions           | 700 x 410 mm          | 700 x 500 mm          |
| Tunnel length                        | 1300 mm               | 1300 mm               |
| Machine weight                       | 350 kg                | 350 kg                |
| Transverse sealing dimensions        | 700 mm                | 700 mm                |
| Sealing-bar opening                  | 330 mm                | 410 mm                |
| Maximum product thickness            | 400 mm                | 400 mm                |
| Maximum roll width                   | 680 mm                | 680 mm                |
| Belt conveyor speed                  | Fixed                 | Fixed                 |
| Motorized film-unwinding             | Top and bottom roll   | Top and bottom roll   |
| Compressed air pressure              | 6 bar                 | 6 bar                 |

Note: Technical data subject to variations without prior notice  
Output depends on the operator and the type of article to be wrapped.



### Arctec (Pty) Ltd.

JHB - 4 Barbeque Terrace, Dytchley Road, Kyalami, Midrand  
Tel: +27 11 466 2468 | Fax: +27 11 466 2080  
CPT - Unit 25 River Edge Business Park, Winelands Close, Stikland, Bellville  
Tel: +27 21 946 4745 | Fax: +27 21 946 2405  
[www.arctec.co.za](http://www.arctec.co.za) | [info@arctec.co.za](mailto:info@arctec.co.za)

