

SPEED BAG H

FAST AND UNEXPENSIVE HORIZONTAL BAGGING



Ideal for wrapping and mailing newspapers and magazines, catalogues and wholesale publications, and any commercial printed materials in A4 size in singlepack. Half-automatic, easy to use: the only thing the operator has to do is simply to feed products horizontally onto the infeed conveyor belt that carries them towards the sealing area. Here a special device will “*clamp*” product and film together and push them through sealing and cutting operations. A bag is formed around the product by the adjustable width folding plates. The bag is then sealed and cut according to the product length.

- Horizontal feeding
- Automatic cycle controlled by PCB
- Display with touch sensitive controls
- Independent sealing-bars; sealing-time and temperature controlled by PCB
- Pneumatic movement, air-compressor inside
- Motorized film-unwinding
- Pneumatic sealing-bar movement driven by internal silent air compressor
- Automatic product ejection
- Synchronous lugged motorized infeed conveyor belt on request
- The machine works with transparent or printed **LLDPE** (thickness 15 ÷ 40)

Machine made according to CE rules

SPECIFICATIONS	SPEED BAG H
Power supply	230 V - 1 Ph - 50/60 Hz
Power required	2 KW
Overall machine dimensions L x W x H	1150 x 750 x 1100 mm
Machine weight	150 kg
Minimum wrapping size L x W x H	230 x 140 x 1 mm
Maximum wrapping size L x W x H	350 x 210 x 10 mm
Maximum film width	500 mm
Output	Up to 1.800 pcs/h