MECTEC

TFS150

TFS150 - Dual Action Tamp

TFS150-Dual Action tamp is a Print & Apply solution especially designed for flexible and reliable Front and Side labelling working from beside the conveyor. The Dual action tamp applies two separate labels with the same applicator and pad.

The TFS150 has the reliable, robust and easy to use design - as seen on all the Mectec family machines. It is proven to give you 24 hours reliable labelling for many years to come!









Handheld terminal TG300 (optional)

TECHNICAL DATA

120 mm

Type of applicator: Tamp/Tamp-Blow. The blow can be

switched off

Tamp size: 150 x 45 mm **Print speed**: Up to 300 mm/sec

Resolution: 8 or 12 dots/mm 200/300 DPI

Interface: 2 x RS232, 1 x USB 2.0

(RS485 and Ethernet optional)

Overall dimensions: 455 x 540 x 630 mm (l x h x w) - P & A

406 x 265 x 128 mm (l x h x w) - PCU III

Controller functions: On-Line and Stand Alone operation,

2 x 20 characters display, 9 keys, 11 status LEDs. 24 Inputs, 26 Outputs. Real time clock, counters, date offsets

and much more...!

FAST FACTS

Printer: 6" Thermal Transfer **Application**: Front and side labelling on

moving object

Label size: 100 x 30 - 160 x 45 mm

Distance: 120 mm

Available in both right- and left hand version!

ACCESSORIES

- TG300 Handheld terminal
- Warning Low Level Media
- Cabinets
- Label Check in the Applicator Pad
- Flashlight/Beacon
- Check scanner
- Fixed or adjustable stands

Manufactured by:

Mectec Elektronik AB

Agnesfridsvägen 189, SE-213 75 Malmö, Sweden P: +46 40 689 25 00 • F: +46 40 689 25 25 info@mectec.se • www.mectec.com

Distributed by: